

# general purpose centrifugal pumps



The J/JB Series Pumps have a heavy-duty cast iron construction and are offered in high and medium head models, with Noryl\* or silicon bronze impeller.

#### APPLICATIONS

Water systems and sprinkling... for homes, farms and industry.

### SPECIFICATIONS

Body and Seal Plate - Close-grained cast iron

Base - Steel 12 gauge

Impeller - J Series - Noryl

Impeller - JB Series - Silicon bronze

Shaft - 416 stainless steel

Mechanical Seal - Carbon/ceramic, Buna-N

# J/JB SERIES

#### FEATURES

1/3 through 2-1/2 HP – High head and medium head models, with heavy-duty motors, easy service design and four-position discharge.

Drain Port – Provided for easy winterizing.

Medium Head Models – Deliver up to 110' of head with capacities to 140 GPM.

**High Head Models** – Deliver up to 140' of head with capacities to 90 GPM.

Easy Serviceability – All models include replaceable wear ring and feature back pull-out design.

J Series with Noryl Impellers – Abrasion-resistant for normal applications with working temperatures to 140°F.

JB Series with Silicon Bronze – JB pumps equipped with shaft seals rated for temperatures to 225°F.

## ORDERING INFORMATION

HIGH HEAD										
Catalog Number			Pipe							
Noryl® Impeller	Silicon Bronze Impeller	НР	Tapping Sizes		Motor		Approx. Wt.			
			Suct.	Disch.	Voltage	Phase	Lbs.			
JHB	JBHB	1/3	1-1/4"	1'	115	1	38			
JHC	JBHC	1/2	1-1/4"	1,	115/230	1	39			
JHC3	JBHC3		1-1/4"	1"	208-230/460	3	39			
JHD	JBHD	3/4	1-1/4*	1,	115/230	1	42			
JHD3	JBHD3		1-1/4"	1,	208-230/460	3	42			
JHE	JBHE	1	1-1/4"	1"	115/230	1	45			
JHE3	JBHE3		1-1/4"	1,	208-230/460	3	45			
JHF	JBHF	1-1/2	1-1/4"	1,	115/230	1	49			
JHF3	JBHF3		1-1/4"	1"	208-230/460	3	49			
JHG	JBHG	2	1-1/2"	1-1/4*	115/230	1	69			
JHG3	JBHG3		1-1/2"	1-1/4"	208-230/460	3	69			
JHHG	JBHHG	2-1/2	2"	1-1/2"	115/230	1	74			
JHHG3	JBHHG3		2"	1-1/2*	208-230/460	3	74			

MEDIUM HEAD									
Catalog Number			Pipe						
Noryl® Impeller	Silicon Bronze Impeller	НР	Tapping Sizes		Motor		Approx. Wt.		
			Suct.	Disch.	Voltage	Phase	Lbs.		
JMB	JBMB	1/3	1-1/4*	15	115	1	38		
JMC	JBMC	1/2	1-1/4"	1"	115/230	1	39		
JMC3	JBMC3		1-1/4"	1"	208-230/460	3	39		
JMD	JBMD	3/4	1-1/4"	15	115/230	1	42		
JMD3	JBMD3		1-1/4"	1"	208-230/460	3	42		
JME	JBME	1	1-1/2"	1-1/4"	115/230	1	43		
JME3	JBME3		1-1/2*	1-1/4*	208-230/460	3	43		
JMF	JBMF	1-1/2	1-1/2"	1-1/4"	115/230	1	54		
JMF3	JBMF3		1-1/2"	1-1/4"	208-230/460	3	54		
JMG	JBMG	2	1-1/2*	1-1/4*	115/230	1	66		
JMG3	JBMG3		1-1/2"	1-1/4"	208-230/460	3	66		
-	JBMMG	2-1/2	2"	1-1/2"	115/230	1	74		
_	JBMMG3		2*	1-1/2*	208-230/460	3	74		

Noryl® is a registered trademark of General Electric Co. PRO-Source™ is a trademark of Pentair Water. In order to provide the best products possible, specifications are subject to change.