



## self-priming centrifugal pump



*The DPC Series self-priming centrifugal pump is a rugged cast iron pump capable of priming up to 20' vertically and will handle solids up to 0.225" diameter. The unit is equipped with a 1/2 HP 115 Volt motor and features 1-1/4" suction and discharge.*

### APPLICATIONS

- Effluent and Wastewater Removal
- Sump Drainage
- Dewatering
- Circulation
- Fountains

### ORDERING INFORMATION

Catalog Number	HP	Volts	Phase/Cycles
DPC	1/2	115	1/60

## DPC SERIES

### SPECIFICATIONS

**Volute** – Cast iron

**Impeller** – Polycarbonate

**Diffuser** – Reinforced polypropylene

**Shaft** – One-piece threaded stainless steel

**Base** – Steel 12 gauge

**Maximum Liquid Temperature**

**Limits** – 130°F (55°C)

### FEATURES

**Motor** – 1/2 HP, 3450 RPM, 115 Volt split phase, 60 Hz. Built-in thermal overload protection with automatic reset.

**Mechanical Seal** – Buna-N elastomers, carbon and ceramic sealing faces, stainless steel metal part.

**Heavy-duty Ball Bearings** – Shielded, permanently lubricated bearings, extensively tested to ensure extended life and smooth, quiet operation.

**Built-in Convenience** – Comes complete with built-in overload protection with automatic reset and a built-in check valve.

**Power Cord** – 10', 115 Volt.

In order to provide the best products possible, specifications are subject to change.