

DE Series

4/10 and 1/2 HP Stainless Steel Continuous Duty Effluent Pump

SPECIFICATIONS

Applications	residential and commercial applications	
Capacities	97 GPM	367 LPM
Shut-off head	36'	11 m
Max. spherical solids	1-1/2"	38 mm
Liquids handling	domestic effluent and drain water	
Continuous liquid temp.	130°F	54°C
Motor electrical data	4/10-1/2 HP, 115V; 4/10 HP, 10.5A; 1/2 HP, 12A; 60Hz	
Acceptable pH range	5-9	
Specific gravity	.9-1.1	
Viscosity	28-35 SSU	
Discharge NPT	2"	
Housing	stainless steel	
Min. sump diameter		
Simplex:	18"	457.2 mm
Duplex:	24"	609.6 mm
Power cord	20', SJOW, 16 AWG	6.1 m

FEATURES

- Pumps up to 97 GPM (1/2 HP) and 92 GPM (4/10 HP)
- Designed to quickly clear water or effluent
- PSC motor with self-lubricating ball-bearing construction
- Ideal for residential and commercial applications
- Tethered float switch
- Double-lip seal with ceramic wear surface
- Suitable for continuous use
- Includes 90° discharge elbow
- CSA Listed

