

DS Series

1/3 through 3/4 HP Stainless Steel Sump Pumps

SPECIFICATIONS

Applications	basement sumps, dewatering, utility	
Capacities	45 GPM	170.3 LPM
Shut-off head	26'	98.4 m
Operation: On	13"	330 mm
Off	6.75"	171 mm
Solids handling	3/4"	19 mm
Liquids handling	drain water	
Continuous liquid temp	104°F	40°C
Motor electrical data	1/3 HP, 2.7A; 1/2 HP, 4.8A; 3/4 HP, 6.4A; 115V; 60Hz, PSC Motor, 3450 RPM	
Acceptable pH range	5-9	
Shaft seal	dual lip with ceramic shaft seal	
Housing	stainless steel	
Power cord	15', SJTW, 18/3	4.6 m
Discharge, NPT	1-1/4"	
Min. sump diameter	12"	305 mm

FEATURES

- Used for dewatering from construction sites, ponds, pits, tanks and extracting water from foundations or flooded basements
- 1/3 HP, 1/2 HP and 3/4 HP available
- PSC motor with self-lubricating ball-bearing construction
- Double lip seals with ceramic wear surface
- Passes 3/4" solids
- Piggyback-style float allows for manual operation
- Includes 1-1/4" NPT x 1-1/4" NPT 90° discharge elbow, 1-1/4" NPT x 1-1/2" NPT adapter
- CSA Listed

